

SPECIALIST WINDOW FILM

Anti Fog Condensation Film

Clear anti-fog performance for trade glazing projects

TRADE ORDERING

Available in 152cm width, by the metre or as a 30m full roll. A 3m minimum applies to per-metre orders.



Anti Fog Condensation Film is a professional-grade specialist window film for trade installations where misting and condensation regularly affect visibility. It is suitable for bathrooms, swimming pools, saunas, cold rooms and other environments where changes in temperature can cause glass or mirrors to fog.

WIDTH**152cm**

trade format

FULL ROLL**30m**

or order by the metre

MINIMUM ORDER**3m**

when buying by the metre

WARRANTY**5 years**

internal warranty

HELPS REDUCE SURFACE FOGGING

Designed to keep treated glazing clearer where misting and condensation affect visibility.

CLEAR SPECIALIST FINISH

Adds anti-fog performance while retaining a discreet appearance on the glass.

TRADE ROLL ORDERING

Available at 152cm wide by the metre or as a complete 30m roll.

SPECIALIST WINDOW FILM

Anti Fog Condensation Film

Technical specification and installation guidance



FILM CONSTRUCTION

Scratch-resistant layer: hard surface layer for durability and easier maintenance.

Polyester layer: high optical quality PET forming the clear film structure.

Adhesive layer: reinforced PS adhesive designed to retain flexibility on impact.

Release liner: protective liner removed during professional installation.

PRODUCT SPECIFICATION	Value
Product type	Anti-fog specialist film
Application	Internal
Film composition	PET
Colour	Transparent
Thickness	60 micron
Visible light transmission	87%
Ultraviolet transmission	1%
Total solar energy rejected	18%
Reduction in solar glare	14%
Trade size	152cm width; by the metre or 30m full roll

GLASS SUITABILITY	Suitability
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
STADIP EXT. clear double pane	Yes
STADIP INT. clear double pane	Yes
Warranty period	5-year internal warranty

APPLICATION GUIDANCE

Professional installation: Apply internally to clean, correctly prepared glass or mirrors using a suitable application solution. Maintenance: clean with a soapy water solution and do not clean for at least a month after installation. Performance depends on correct installation, surface condition, environmental conditions and aftercare.