

DECORATIVE WINDOW FILM

Decorative Window Film Perla

Decorative trade window film projects

TRADE ORDERING

Choose the 152cm by-the-metre option for cut lengths, or the 30m full roll for larger and repeat installations. A 3m minimum applies to per-metre orders.



Decorative Window Film Perla is a decorative window film for professional installation on glass, partitions and interior glazing. Use it to add colour, texture, pattern or visual interest to commercial and domestic spaces without replacing existing glass.

WIDTH**152cm**

trade format

FULL ROLL**30m**

or order by the metre

MINIMUM ORDER**3m**

when buying by the metre

WARRANTY**5 years**

internal warranty

REFINED DECORATIVE FINISH

Introduces subtle pattern and texture to clear glass without replacing the glazing.

CLIENT-FACING INTERIORS

Well suited to reception areas, partitions, doors and decorative feature panels.

152CM TRADE FORMAT

Order cut lengths by the metre or select a 30m full roll for larger projects.

DECORATIVE WINDOW FILM

Decorative Window Film Perla

Technical specification and installation guidance



FILM CONSTRUCTION

Decorative layer: high optical quality polyester with printed Perla design.
Adhesive layer: PS adhesive, with glass polymerization within 15 days.
Release liner: protection release liner, disposable after installation.

PRODUCT SPECIFICATION	Value
Product type	Decorative window film
Pattern	Perla
Application	Internal
Thickness	40 µ
Composition	PET
Colour	Decorative / frosted
Width	152cm
Trade size	By the metre or 30m full roll
Minimum order	3m per-metre orders
Fire resistance rating	M1

GLASS SUITABILITY	Suitability
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
STADIP EXT. clear double pane	Yes
STADIP INT. clear double pane	Yes
Warranty period	5-year internal warranty

APPLICATION GUIDANCE

Professional installation: Apply internally to clean, correctly prepared glass using a suitable application solution.
Maintenance: use a soapy water solution and do not clean for at least a month. Performance and warranty depend on correct installation, surface condition and aftercare.