

DECORATIVE WINDOW FILM

Reeded glass-effect privacy film

Reeded Glass Window Film

A decorative glass-effect film that recreates the timeless look of reeded glazing while diffusing views and allowing natural light to pass.



About Reeded Glass Window Film

Reeded Glass Window Film recreates the elegant appearance of fluted and textured glass on existing glazing. It softens the view through the pane while allowing high levels of natural light to pass, making it a practical decorative privacy solution for homes, offices, bathrooms, partitions and internal glass features.

Available across a choice of flute widths, colours, finishes and fitting types, the range offers a flexible way to achieve a premium textured-glass appearance without replacing the glass.

Trade ordering note: Product construction, colour, flute width and fitting method vary across the reeded range. Select the required product before ordering and follow its individual installation guidance.

At a glance

Visible light transmission

90%

Ultraviolet transmission

0.5%

Warranty

Up to 10 years

Installation type

Interior

Finish

Reeded / fluted

Roll length

Various

Decorative reeded glass-effect film combining high light transmission with obscured vision for a clean, contemporary privacy finish.

Diffused privacy

Obscures direct views while allowing natural light through.

Multiple styles

Available in different flute widths, colours and finishes.

Flexible application

Suitable for decorative interior glazing in domestic and commercial spaces.

Technical datasheet

Figures are based on the supplied technical data for the standard reeded film applied to clear 3mm glass on double glazing 4-16-4. Exact properties can vary between finishes and fitting types.

Technical properties

Property	Value
Ultraviolet transmission	0.5%
Visible light transmission	90%
Reflection of external visible light	9%
Reflection of internal visible light	9%
Total solar energy rejected	14%
Total solar energy rejected 2*	15%
Solar energy reflection	9%
Solar energy absorption	7%
Solar energy transmission	84%
Reduction in solar glare	13%
g-value	0.85
u-value	-
Shading coefficient	0.9

Product characteristics

Characteristic	Value
Warranty	Up to 10 years
Fire resistance rating	M1
Storage in recommended conditions	3 years
REACH / RoHS	Compliant
Installation type	Interior
Roll length	Various
Composition	PET
Thickness	50 microns
Colour / finish	Varies by product
Fitting method	Self-adhesive or

Application advice

Vertical installation on standard glass surfaces.

Glass type	Advice
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	Yes
Reflective tinted double pane	Yes
Gas-filled double pane - Low E	Yes
STADIP EXT. clear double pane	Yes
STADIP INT. clear double pane	Yes

Construction and specification

Construction varies across the range. Self-adhesive versions typically use high-quality PET, a protective surface layer, pressure-sensitive adhesive and a removable liner. Static-cling products use a non-adhesive cling layer. Refer to the selected product listing for exact details.

Installation and maintenance

Install to clean glass using the method specified for the selected product. Use a mild soapy-water fitting solution where required. Do not clean newly installed film for at least one month and avoid abrasive cleaners, blades or scouring pads.

Recommendations are based on a glazed surface covering up to 2.5m². Exact performance, fitting method, warranty and appearance can vary between individual reeded products. Contact Window Films Direct for confirmation where required. Non-contractual data; product composition may be modified at any time.