

REUSABLE PRIVACY WINDOW FILM

Reusable Static Cling Film Range

TRADE ORDERING

Static Cling Frost is supplied in 122cm or 152cm widths as 10m lengths or 20m full rolls. Static Cling Blackout is available at 122cm wide by the metre or as a 20m full roll; a 3m minimum applies to per-metre orders.

**Static Cling Frost**

Reusable frosted privacy without adhesive.

**Static Cling Blackout**

Reusable dark privacy film for temporary or changeable installations.

A reusable, adhesive-free film range that can be installed, removed and repositioned. Choose the frosted finish for diffused privacy or the darker blackout option for stronger screening and solar control.

FROSTED**76% VLT**

20% glare reduction

BLACKOUT**72% solar energy rejected**

100% glare reduction

APPLICATION**Reusable****ADHESIVE****None****WARRANTY****5 years****ROLL LENGTH****Up to 20m**

TECHNICAL COMPARISON

Product performance

Performance property	Static Cling Frost	Static Cling Blackout
Ultraviolet transmission	>25%	1%
Visible light transmission	76%	<1%
External visible-light reflection	15%	13%
Internal visible-light reflection	15%	13%
Total solar energy rejected	18%	72%
Total solar energy rejected* (4-16-4)	19%	65%
Solar energy reflection	10%	11%
Solar energy absorption	17%	88%
Solar energy transmission	73%	1%
Reduction in solar glare	20%	100%
g-value	0.77	0.26
u-value	5.6	-
Shading coefficient	NC	0.2

Static Cling Frost: 100-micron frosted monomer PVC with no adhesive, supplied as a reusable privacy film that retains a high level of natural light.

Static Cling Blackout: 100-micron black PVC static-cling film with no adhesive, providing near-total visible-light exclusion and 100% solar-glare reduction.

Shared characteristics: 20m roll length, internal application and removable, reusable construction.

GLASS COMPATIBILITY

Installation guidance

Static-cling films rely on clean, smooth glazing and water-assisted application. Use the compatibility matrix as a guide and confirm specialist glazing before fitting.

Glazing type	Static Cling Frost	Static Cling Blackout
Clear single pane	Yes	Caution
Tinted single pane	Yes	No
Reflective tinted single pane	Yes	Yes
Clear double pane	Yes	Caution
Tinted double pane	Yes	No
Reflective tinted double pane	Yes	Yes
Gas-filled double pane - Low E	Yes	No
Laminated ext. clear double pane	Yes	No
Laminated int. clear double pane	Yes	No

Installation

Clean the glass thoroughly and apply with a fine mist of water. Position the film, remove trapped water with a soft squeegee and allow it to settle. No adhesive is used, so the film can be removed and reused.

Care

Avoid abrasive cleaners and sharp tools. Store removed film flat or carefully rolled with the protective liner where available. Do not install on damaged or uneven glazing.