

FROSTED WINDOW FILM

Standard Frosted Window Film

Trade privacy and frosted glass installations

TRADE ORDERING

Choose 100cm, 122cm or 152cm width, supplied in 10m lengths or as a 50m full roll.



Standard Frosted Window Film is a trade window film for creating privacy, screening or a frosted-style finish on glass. It is well suited to offices, meeting rooms, residential glazing, partitions and commercial interiors where privacy is needed without replacing the glass.

WIDTH OPTIONS**100, 122 or 152cm**

trade size options

ROLL LENGTH**10m**

supplied in practical trade lengths

FULL ROLL**50m**

full roll option available

WARRANTY**10 years**

internal warranty

CLEAN FROSTED PRIVACY

Creates a consistent translucent finish for partitions, doors, bathrooms and office glazing.

LIGHT-DIFFUSING FINISH

Screens direct views while allowing useful natural light into the space.

IDEAL FOR INTERIORS

Suitable for offices, homes, partitions and client-facing interiors.



FROSTED WINDOW FILM

Standard Frosted Window Film

Technical performance and installation guidance



FILM CONSTRUCTION

Frosted film layer: 100µ frosted monomer PVC for privacy and decorative screening.

Adhesive layer: half permanent adhesive, helping limit adhesive transfer during removal.

Liner: disposable plastic liner or silicone paper liner suitable for digital cutting.

PRODUCT SPECIFICATION	Value	GLASS SUITABILITY	Suitability
Product type	Frosted privacy film	Clear single pane	Yes
Application	Internal	Tinted single pane	Yes
Thickness	100 µ	Reflective tinted single pane	Yes
Composition	PVC	Clear double pane	Yes
Colour	Frosted	Tinted double pane	Yes
Visible light transmission	76 %	Reflective tinted double pane	Yes
Total solar energy rejected	18 %	Gas-filled double pane - Low E	Yes
Reduction in solar glare	20 %	STADIP EXT. clear double pane	Yes
Ultraviolet transmission	>25 %	STADIP INT. clear double pane	Yes
Trade size	100cm, 122cm or 152cm widths; 10m lengths or 50m full roll	Warranty period	10-year internal warranty

APPLICATION GUIDANCE

Professional installation: Apply internally to clean, correctly prepared glass using a suitable application solution.

Maintenance: use a soapy water solution and do not clean for at least a month. Performance and warranty depend on correct installation, surface condition and aftercare.