

TRANSPARENT WINDOW FILM

Transparent Coloured Window Film Range

Eleven vivid colours for interior glazing

TRADE ORDERING

Available in 152cm width, by the metre or as a 30m full roll. A 3m minimum applies to per-metre orders.



Transparent Coloured Window Film adds vivid colour to interior glazing while retaining the clear, open character of the glass. It is suitable for partitions, feature glazing, shower screens, displays and decorative interior applications.

AVAILABLE COLOURS**11**

range options

VISIBLE LIGHT**45%**

Yellow reference

GLARE REDUCTION**60%**

Yellow reference

WARRANTY**5 years**

internal application

Available colours



Range note: This specification sheet covers Azure Blue, Ocean Blue, Lime Green, Orange, Pink, Plum, Purple, Raspberry, Red, Turquoise and Yellow. Appearance and optical performance can vary by colour.

TRANSPARENT WINDOW FILM

Transparent Coloured Window Film Range

Technical performance and application data

REPRESENTATIVE TECHNICAL DATA

The figures below are the supplied Yellow reference data. Other colours may differ in visible-light transmission, reflection, glare reduction and solar performance.

Technical property	Value	Glass type	Advice
Ultraviolet transmission	1%	Clear single pane	Yes
Visible light transmission	45%	Tinted single pane	Yes
Reflection of external visible light	9%	Reflective tinted single pane	Yes
Reflection of internal visible light	9%	Clear double pane	Yes
Total solar energy rejected	22%	Tinted double pane	Yes
Total solar energy rejected*	25%	Reflective tinted double pane	Yes
Solar energy reflection	9%	Gas-filled double pane - Low E	Yes
Solar energy absorption	18%	STADIP EXT. clear double pane	Yes
Solar energy transmission	73%	STADIP INT. clear double pane	Not recommended
Reduction in solar glare	60%		
u-value	5.7		
Installation type	Internal application		
Roll length	30.5m		
Composition	PET		
Thickness	40 micron		
Reference colour	Yellow		

CONSTRUCTION

1. Hard scratch-resistant layer for durability and ease of maintenance during window cleaning.
2. Dyed polyester without optical distortion.
3. PS adhesive, glass polymerisation within 15 days.
4. Protection release liner, disposable after installation.

INSTALLATION AND MAINTENANCE

Install to clean glazing using a suitable soapy-water fitting solution. Do not clean the film for at least one month after installation. Confirm colour choice and glazing suitability before ordering or installation.